

## 21.5 inch Panel PC ARCHMI-921P



- 21.5" HD1080 TFT LCD graphics display 1920 x 1080 pixels
- Processor: Intel® Core™ i3-4010U (1.7 GHz)
- Die-cast aluminum housing
- Flush frame design, IP66 front side
- Fanless cooling system
- Horizontal viewing angle 178°, vertical 178°

<https://www.wachendorff-prozesstechnik.de/en/archmi-921p>

### Description

The ARCHMI-9 series is based on Intel Core-i processors

This very powerful and efficient processor family provides sufficient computing power for medium and large applications. The RAM can be expanded to up to 8 GB, enabling more extensive projects such as SCADA or IIoT monitor control applications. The Panel PCs in this series are available in display sizes ranging from 12.1" to 32", with a choice of projected capacitive or resistive touch. The projected capacitive touch enables multi-touch operation with a corresponding operating system. If pressure-sensitive operation is required (e.g. with gloves), the resistive touch is the right choice. The front panels are absolutely flush with the die-cast aluminum housing. The housing is IP66 rated. The unique fanless thermal design of the die-cast aluminum housing enables effective temperature control. The ARCHMI IPC can be optionally equipped with a high-brightness LCD and/or optical bonding for an outstanding display, even under difficult conditions. Expansion cards for additional interfaces or WLAN can also be integrated.

### Product details

|                    |  |
|--------------------|--|
| Power supply:      | 9 VDC to 36 VDC  |
| Power consumption: | max. 53 W  |
| Display:           | 21.5" TFT LCD  |
| Resolution:        | 1920 x 1080 pixels   |
| Aspect ratio:      | 16:9   |
| Brightness:        | 250 cd/m <sup>2</sup>  |
| Colors:            | 16,7 M   |
| Reading angle:     | H: 178° / V: 178°  |
| Touch screen:      | projects capacitively  |
| Processor:         | Intel® Core™ i3-4010U (1.7 GHz)<br>Intel® Core™ i5-4310U (up to 3 GHz)   |
| RAM:               | 4 GB DDR3L 1600 MHz onboard  |
| SSD/HDD:           | 1x SATA2 2.5"  |
| Additional memory: | 1x SD card slot up to 32 GB.   |
| Interfaces:        | USB: 2x USB 3.0 type A<br>Serial: COM1: RS232 / RS422 / RS485; COM2: RS232<br>Ethernet: 2x GbE 10/100/1000 Base T (X), RJ45<br>Power supply: pluggable 3-pin terminal strip<br>On/off switch: optional plug-in 2-pin terminal strip, see accessories<br>IPC_DIO_2P |
| Expansion slots:   | 1 x Mini PCIe half-height (internal)<br>Audio: 3.5 mm jack   |

|                     |  |
|---------------------|--|
| Housing:            | Die-cast aluminum  |
| Assembly:           | VESA 100 x 100; panel mounting   |
| Protection class:   | IP66 on the front  |
| Weight:             | approx. 7.5 kg   |
| Ambient conditions: | Operation: 0 °C to +50 °C<br>Storage: -30 °C to +70 °C<br>10 % to 90 % r.H, non-condensing   |
| Certifications:     | CE/FCC Class A, CB, UL   |
| Operating systems:  | Windows 7 Professional for Embedded Systems (FES) 32 Bit<br>Windows 7 Ultimate for Embedded Systems (FES) 32 Bit<br>Windows 7 Professional for Embedded Systems (FES) 64 Bit<br>Windows 7 Ultimate for Embedded Systems (FES) 64 Bit<br>Windows Embedded Standard 7 (P)<br>Windows® Embedded 8.1 Industry Pro (ESD) 32 Bit<br>Windows® Embedded 8.1 Industry Pro (ESD) 64 bit<br>Windows 10 IoT Enterprise 2015 (ESD) 32 bit<br>Windows 10 IoT Enterprise 2015 (ESD) 64 bit<br>Windows 10 IoT Enterprise LTSC 2016 (ESD) (for i3/i5) |
| Options:            | VGA<br>HDMI<br><br>2 x USB 2.0<br>2 x USB 2.0 + 1x LAN<br>2 x USB 2.0 + 1x COM<br>2 x USB 2.0 + 1x HDMI<br>2 x USB 2.0 + 1x COM + 1x Power Switch + 1x Mini PCIe slot full size<br>2 x COM<br>2 x CAN (on request)<br><br>WLAN 2.4GHz ,BT4<br>WLAN 2.4GHz, 5GHz, BT4<br><br>Optical bonding<br>High Brightness Display<br>Smart Battery  |
| Scope of delivery:  | Device<br>1 x seal<br>1 x Mounting material<br>1 x plug-in power supply unit   |
| Manufacturer:       | Aplex Technology Inc.  |


**Drawings**

**Dimensions (mm):**

**Abmessungen:**

**Maße: mm**

**Toleranz: ±0,5mm**



**Downloads / FAQ**

The following files could be downloaded from our website directly from this product under the tab "Drawings":

**2D drawing Panel-PC ARCHMI-921**

Panel-PC-ARCHMI-X21.dwg



Wachendorff Prozesstechnik GmbH & Co. KG  
Industriestrasse 7 • 65366 Geisenheim  
Germany

Phone: +49 (0) 67 22 / 99 65 - 20  
E-Mail: [wp@wachendorff.de](mailto:wp@wachendorff.de)  
[www.wachendorff-prozesstechnik.de](http://www.wachendorff-prozesstechnik.de)

