WACHENDORFF
Prozesstechnik GmbH & Co. KG

Gateway BACnet/IP Server / CAN
HD67677-IP-A1

Abbildungen ähnlich

- Read and write up to 2,000 BACnet objects
- Read and write up to 500 CAN frames
- High temperature range from -40 °C to +85 °C
- Galvanic 3-way isolation between BACnet / CAN and power supply
- Transmission of project planning via Ethernet

https://www.wachendorff-prozesstechnik.de/en/HD67677-IP-A1

Description
Further information on this gateway is available on request. Please get in touch with the contact persons listed below.

Product details	
Interfaces:	1x CAN (removable screw terminal, 3-pin) 2x Ethernet port (RJ45 socket)
BACnet objects:	Read and write up to 2,000 BACnet objects
CAN data rate:	Read and write up to 500 CAN frames
LED:	6x signal display for supply and communication
Supply:	12 VDC to 35 VDC or 8 VAC to 24 VAC
Power consumption:	HD67677-IP-A1: 3.5 Watt / VA
Software:	Free configuration software SW67677 for parameterization of the device
BBMD functionality:	This gateway only supports BBMD in a rudimentary way. No "Registration by Foreign Devices" and no NAT.
Operating temperature:	-40 °C to +85 °C
Humidity:	10 % to 80 %, non-condensing
Housing:	Previous housing: PVC New housing: PC-ABS
Dimensions (WxHxD):	Previous housing: 23 mm x 107 mm x 120 mm New housing: 22.5 mm x 90.7 mm x 123 mm
Weight:	approx. 200 g
Fastening:	Mounting on the DIN rail
Note:	**The article description should always be viewed from the gateway's perspective.** You can connect **masters** to the **HD67677** on the BACnet side.
Customs tariff number:	8517 62 00
Manufacturer:	ADFweb.com S.r.l.

Products Order no.	
HD67677-IP-A1	Gateway BACnet/IP Server / CAN

Accessories Order no.	
DRS3-24	Power supply unit for top-hat rail, 85 to 264 VAC, 24 VDC 3 A, spring terminal
DRS4-24A	Power supply unit for top-hat rail, 85 to 264 VAC, 24 VDC 4.2 A, screw terminal
KABETH10	Patch cable, RJ45 UTP CCA, CAT5e white, 0.3 m
KABETH11	Patch cable, RJ45 UTP CCA, CAT5e white, 1 m
KABETH12	Patch cable, RJ45 UTP CCA, CAT5e white, 2 m

Drawings

Example application

Drawings

Dimensions (previous housing)

Gehäuse: PVC
Gewicht: ca. 200g

Drawings

Dimensions (new housing)

Gehäuse: PC-ABS
Gewicht: ca. 200g

Drawings

Connection diagram

WACHENDORFF
Prozesstechnik GmbH & Co. KG

Wachendorff Prozesstechnik GmbH & Co. KG
Industriestrasse 7 • 65366 Geisenheim
Germany

Phone: +49 (0) 67 22 / 99 65 - 20
E-Mail: wp@wachendorff.de
www.wachendorff-prozesstechnik.de