

Gateway BACnet/IP Client / Profibus Slave HD67716-IP-A1



Abbildungen ähnlich

- Read and write up to 512 BACnet objects
- Profibus data block size maximum 244 bytes
- Data exchange between BACnet and Profibus
- Galvanic 3-way isolation between BACnet / Profibus and power supply
- Transmission of project planning via Ethernet

<https://www.wachendorff-prozesstechnik.de/en/HD67716-IP-A1>

Description

Further information on this gateway is available on request. Please get in touch with the contact persons listed below.

Product details

Interfaces:	1x Profibus (Sub-D socket, 9-pin) 2x Ethernet port (RJ45 socket)
BACnet objects:	Read and write up to 512 BACnet objects
Profibus data block size:	Input block maximum 244 bytes Output block maximum 244 bytes
LED:	6x signal display for supply and communication
Supply:	12 VDC to 35 VDC or 8 VAC to 24 VAC
Power consumption:	HD67716-IP-A1: 3.5 Watt / VA
Software:	Free configuration software SW67716 for parameterization of the device.
BBMD functionality:	This gateway only supports BBMD in a rudimentary way. No "Registration by Foreign Devices" and no NAT.
Profibus GSD file:	You can generate the required Profibus GSD file with the free free configuration software SW67716.
Operating temperature:	-40 °C to +85 °C
Humidity:	10 % to 80 %, non-condensing
Housing:	Previous housing: PVC New housing: PC-ABS
Dimensions (WxHxD):	Previous housing: 23 mm x 107 mm x 120 mm New housing: 22.5 mm x 90.7 mm x 123 mm
Weight:	approx. 200 g
Fastening:	Mounting on the DIN rail
Note:	The article description should always be viewed from the gateway's perspective. You can connect slaves to the HD67716 on the BACnet side and masters on the Profibus side.
Customs tariff number:	8517 62 00
Manufacturer:	ADFweb.com S.r.l.

Products Order no.


HD67716-IP-A1	Gateway BACnet/IP Client / Profibus Slave
---------------	---

Accessories Order no.

DRS3-24	Power supply unit for DIN rail, 85 to 264 VAC, 24 VDC 3 A, spring terminal
DRS4-24A	Power supply unit for DIN rail, 85 to 264 VAC, 24 VDC 4.2 A, screw terminal
KABETH10	Patch cable, RJ45 UTP CCA, CAT5e white, 0.3 m
KABETH11	Patch cable, RJ45 UTP CCA, CAT5e white, 1 m
KABETH12	Patch cable, RJ45 UTP CCA, CAT5e white, 2 m


Drawings

Example application



Drawings


Dimensions (previous housing)



Gehäuse: PVC
Gewicht: ca. 200g

Drawings

Dimensions (new housing)



Gehäuse: PC-ABS
Gewicht: ca. 200g



Wachendorff Prozesstechnik GmbH & Co. KG
Industriestrasse 7 • 65366 Geisenheim
Germany

Phone: +49 (0) 67 22 / 99 65 - 20
E-Mail: wp@wachendorff.de
www.wachendorff-prozesstechnik.de

