

Gateway OPC UA Server (Slave) / Serial HD67B26-X-B2



Abbildung ähnlich

- Bidirectional data exchange between serial and OPC UA
- High temperature range from -40 °C to +85 °C
- Transmission of project planning via Ethernet

<https://www.wachendorff-prozesstechnik.de/en/HD67B26-X-B2>

Description

The HD67B26-X-B2 is an OPC UA Server (Slave) / Serial Gateway and enables the reading/writing of data from one or more serial devices to make them available to an OPC UA network. This gateway is very easy to configure and allows you to connect an OPC UA system to the serial world. Further information on this gateway is available on request. Please get in touch with the contact persons listed below.

Product details

Interfaces:	HD67B26-2-B2: 1x Ethernet port (RJ45 socket) 1x RS232 (screw terminal, 3-pin)
	HD67B26-5-B2: 1x Ethernet port (RJ45 socket) 1x RS485 (screw terminal, 3-pin)
Serial data rate:	Up to 115,200 bps
OPC-UA data rate:	10/100 Base-T, automatic detection
LED:	5x signal display for supply and communication
Supply:	12 VDC to 35 VDC or 8 VAC to 24 VAC
Power consumption:	HD67B26-X-B2: 4 Watt/ VA
Software:	Free SW67B26 configuration software for parameterization of the device
Operating temperature:	-40 °C to +85 °C
Humidity:	10 % to 80 %, non-condensing
Housing:	PVC
Dimensions (WxHxD):	35 mm x 95 mm x 60 mm
Weight:	approx. 200 g
Fastening:	Mounting on the DIN rail
Customs tariff number:	8517 62 00
Manufacturer:	ADFweb.com S.r.l.

Products Order no.

HD67B26-2-B2	Gateway OPC UA Server (Slave) / Serial RS232
HD67B26-5-B2	Gateway OPC UA Server (Slave) / Serial RS485

Accessories Order no.

AMR4-24	DIN rail power supply unit for building automation, 90 to 264 VAC, 24 VDC, 2.5 A
KABETH10	Patch cable, RJ45 UTP CCA, CAT5e white, 0.3 m
KABETH11	Patch cable, RJ45 UTP CCA, CAT5e white, 1 m
KABETH12	Patch cable, RJ45 UTP CCA, CAT5e white, 2 m



Wachendorff Prozesstechnik GmbH & Co. KG
Industriestrasse 7 • 65366 Geisenheim
Germany

Phone: +49 (0) 67 22 / 99 65 - 20
E-Mail: wp@wachendorff.de
www.wachendorff-prozesstechnik.de

