

Ethernet switch, 8 ports, Gigabit - ETHSWG80T



- 8x 10/100/1000BaseT(X)
- Unmanaged / Plug and Play
- IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x
- IEEE 802.1p: CoS, 4 queues per port
- Supports jumbo frames up to 9000 bytes
- Broadcast and multicast flooding storm control
- Redundant voltage input
- Operating temperature -40 °C to +75 °C
- Protection class IP30

<https://www.wachendorff-prozesstechnik.de/en/ethswg80t>

Description

The ETHSWG80T is a very compact and robust Industrial Ethernet switch with 8x 10/100/1000BaseT(X). In addition to IEEE 802.3, IEEE802.3u, IEEE 802.3ab and IEEE802.3x, CoS according to IEEE 802.1p is also supported. Four queues (priority classes) are available per port for this purpose. The compact, IP30-certified housing was developed for use in harsh and demanding industrial environments where large temperature differences and physical stresses are known to occur.

The ETHSWG80T is an unmanaged and plug and play-capable switch with a non-blocking/wirespeed Layer 2 switching engine. Secure transmission is guaranteed thanks to the Store and Forward operating mode. The switchable Flooding Storm Control function protects against unwanted occupation of the available transmission rate by broad or multicast data frames.

With Auto Power Savings and the IEEE 802.3az Energy Efficient Ethernet (EEE) protocol, the ETHSWG80T can automatically detect the cable connection status and network traffic and adjust its power consumption accordingly. With less device activity, the switch consumes less power and thus achieves higher energy efficiency.

Power consumption:	2.88 watts
Operating temperature:	-40 °C to +75 °C (cold start at -40 °C)
Storage temperature:	-40 °C to +85 °C
Humidity:	5 % to 95 % rH (non-condensing)
FCC/EMI:	FCC Part 15 Class A/CE
Vibration:	IEC60068-2-6
Shock:	IEC60068-2-27
Free fall:	IEC60068-2-32
RoHS and WEEE:	compliant
Protection class:	IP30
Execution:	Robust metal housing
Dimensions (WxHxD):	41 mm x 115 mm x 70 mm
Weight:	305 gram
Assembly:	DIN rail or wall mounting
Scope of delivery:	Device, terminal strip connector, DIN rail holder, wall mounting bracket, installation sheet
Manufacturer:	Planet Technology Corporation

Product details

Operating mode:	Store and Forward
Switching engine:	wire-speed / non-blocking
EtherNet standards:	• IEEE 802.3 (10BaseT) • IEEE 802.3u (100BaseTX) • IEEE 802.3ab (1000BaseTX) • IEEE 802.1p (CoS) • IEEE 802.3x (Full Duplex) and Back-Pressure (Half Duplex) • IEEE 802.3az Energy Efficient Ethernet (EEE) • Jumbo Frames 9K
RJ45 ports:	8x 10/100/1000BaseT(X)
RJ45 - Speed:	Auto-negotiation (10/100/1000 Mbit/s)
RJ45 - Duplex:	Half or full duplex
RJ45 connection:	MDI/MDIX Auto-Crossover
MAC table size:	4K
Display:	2x Power status: P1, P2 - Power supply status 8x Ethernet port status: Link & Speed
Power supply:	Redundant input terminal block connector with reverse polarity protection
Voltage range:	9 to 48 VDC / 24 V AC

Products Order no.

ETHSWG80T	8-way Ethernet switch, Gigabit, unmanaged
-----------	---

Accessories Order no.

DRS4-24A	Power supply unit for top-hat rail, 85 to 264 VAC, 24 VDC 4.2 A, screw terminal
CPNLRJ45	RJ45 to RJ45 panel connector / panel front IP 68
KABETH10	Patch cable, RJ45 UTP CCA, CAT5e white, 0.3 m
KABETH11	Patch cable, RJ45 UTP CCA, CAT5e white, 1 m
KABETH12	Patch cable, RJ45 UTP CCA, CAT5e white, 2 m



Wachendorff Prozesstechnik GmbH & Co. KG
Industriestrasse 7 • 65366 Geisenheim
Germany

Phone: +49 (0) 67 22 / 99 65 - 20
E-Mail: wp@wachendorff.de
www.wachendorff-prozesstechnik.de

