

23.8 inch Panel PC ARCHMI-824BP



- 23.8" TFT LCD, 1920 x 1080 pixels (FHD)
- Projected capacitive touch
- Processor: Intel® Celeron® J6412 (2.0 GHz)
- Fanless cooling system
- Reading angle horizontal 178°, vertical 178°

<https://www.wachendorff-prozesstechnik.de/ARCHMI-S-824BP>

Description

The ARCHMI-S-824BP series is based on an Intel® Celeron® J6412 processor with 2.0 GHz.

The industrial panel PCs in the ARCHMI-S-824BP series are equipped with a 23.8-inch TFT LCD display with a projected capacitive touchscreen. The projected capacitive touch enables multi-touch operation with a corresponding operating system. The front panels are absolutely flush with the die-cast aluminum housing. The front of the housing is IP66 rated. The unique fanless thermal design of the die-cast aluminum housing enables effective temperature control. The ARCHMI-IPC can be optionally equipped with a high brightness LCD and/or optical bonding for an outstanding display, even under difficult conditions. This high-performance yet highly energy-efficient processor family is used, for example, in factory automation, remote data acquisition and the most common industrial applications.

Product details

Power supply:	9 VDC to 36 VDC
Power consumption:	tbd
Display:	23.8" TFT LCD
Resolution:	1920 x 1080 pixels(FHD)
Aspect ratio:	16:9
Brightness:	250 cd/m ² 1000 cd/m ² (optional high-brightness LCD)
Backlight:	30,000 h running time
Colors:	16,7 M
Reading angle:	H: 178° / V: 178° H: 178° / V: 178° (optional high-brightness LCD)
Touch screen:	Projected capacitive touch
Processor:	Intel Celeron J6412 Processor (2.0 GHz)
RAM:	1 x 260-pin SO-DIMM up to 32GB DDR4 3200MHz
SSD/HDD:	1 x M.2 B-Key slot; (Support SATA3; 2242/2280)

Interfaces:	USB: 2 x USB 3.2 type A / 2x USB 2.0 type A Serial: RS-485/422/232 (COM1, BIOS selection, RS-232 by default), 1x DB9 RS-232 Ethernet: 1 x RJ45 type Intel I210AT 1GbE LAN, 1 x RJ45 type Intel I225LM/I226LM 2.5GbE LAN Audio: Line out 3.5 mm jack Power supply: pluggable 3-pin terminal strip On/off switch: optional pluggable 2-pin terminal strip
Expansion slots	1 x Mini PCIe slot 1x M.2 E-Key 2230 for WiFi/Bluetooth module (USB 2.0, PCIe 3.0 x1) 1 x micro SIM card slot
Housing:	Die-cast aluminum
Assembly:	VESA 100 x 100; panel mounting
Protection class:	IP66 on the front
Dimensions (WxHxD):	640 mm x 395mm x 88 mm
Weight:	9.43 Kg
Ambient conditions:	Operation: 0 °C to +50 °C Storage: -30 °C to +70 °C 10% to 95 %rH, non-condensing.
Certifications:	CE/FCC Class A
Operating systems:	Windows® 10 IoT Ent 2021 LTSC Windows® 11(21H2) or later Linux 18.04 or later
Scope of delivery:	Device 1 x power supply unit 1 x mounting material
Customs tariff number:	84715000
Manufacturer:	Aplex Technology Inc.

Products Order no.

ARCHMI-S-824BP	23.8" Industrie-Panel-PC, projiziert-kapazitiver Touch
----------------	--


Accessories Order no.

ETHSWG5C	5-fach Ethernet Switch, Gigabit, unmanaged
ETHSWG8C1	8-port Ethernet switch, Gigabit, unmanaged

KABETH10	Patch-Kabel, RJ45 UTP CCA, CAT5e weiß, 0,3 m
KABETH11	Patch-Kabel, RJ45 UTP CCA, CAT5e weiß, 1 m
KABETH12	Patch-Kabel, RJ45 UTP CCA, CAT5e weiß, 2 m
IPC_DIO_2P	Anschlusstecker 2-polig, digitaler Eingang

Drawings

Dimensions (mm):





Wachendorff Prozesstechnik GmbH & Co. KG
Industriestrasse 7 • 65366 Geisenheim
Germany

Phone: +49 (0) 67 22 / 99 65 - 20
E-Mail: wp@wachendorff.de
www.wachendorff-prozesstechnik.de

