


18.5 inch display FABS-118R suitable for food production



- 18.5" TFT LCD, 1366 x 768 pixels
- resistive touch
- IP66/IP69K-compliant front panel
- Fanless cooling system
- Reading angle horizontal 170°, vertical 160

<https://www.wachendorff-prozesstechnik.de/en/FABS-118R>

Description

The FABS-1 series has a stainless steel housing that can be certified in accordance with EN 1672-2 (not certifiable for the resistive touch). The industrial displays in this series, which are suitable for food production, are available in display sizes from 7" to 21.5" and are optionally equipped with touch. The projected capacitive touch enables multi-touch operation. The display is absolutely flush with the stainless steel front panel (type 304). The front has an IP66 (incl. IP66) rating and the fanless thermal design of the robust housing enables effective temperature control. The FABS displays can be optionally equipped with a high-brightness LCD and/or optical bonding for an outstanding display, even under the most difficult conditions.

Product details

Power supply:	9 VDC to 36 VDC
Power consumption:	max. 18 W
Display:	18.5" TFT LCD
Resolution:	1366 x 768
Aspect ratio:	4:3
Brightness:	300 cd/m ² 1000 cd/m ² (High Brightness Optional)
Colors:	16.7 million
Reading angle:	H: 170 / V: 160°
Backlight:	50.000 h
Touch screen:	resistive
Interfaces:	Video: 1 x VGA, 1 x DVI, 1 x DP, 1 x HDMI Audio: 3.5 mm jack input Power supply: pluggable 3-pin terminal strip
Housing:	Die-cast aluminum Stainless steel front panel (type 304, optionally 316)
Assembly:	VESA 100 x 100; panel mounting
Protection class:	IP66/IP69K (front)
Dimensions (WxHxD):	510 mm x 325 mm x 63.7 mm
Weight:	approx. 6.58 kg
Ambient conditions:	Operation: 0 °C to +50 °C ; Storage: -30 °C to +70 °C 10% to 90 % r.H, non-condensing.
Certifications:	CE/FCC Class A

Options:	Optical bonding High Brightness Display Extended temperature range -20°C to +60°C
Scope of delivery:	Device 1 x power supply unit 1 x mounting material
Customs tariff number:	85285210
Manufacturer:	Aplex Technology Inc.

Products Order no.


FABS-118R	18.5" industrial display, stainless steel front panel, resistive touch
-----------	--

Accessories Order no.

ETHSWG5C	5-way Ethernet switch, Gigabit, unmanaged
ETHSWG8C1	8-port Ethernet switch, Gigabit, unmanaged
DRS4-24A	Power supply unit for DIN rail, 85 to 264 VAC, 24 VDC 4.2 A, screw terminal
KABETH10	Patch cable, RJ45 UTP CCA, CAT5e white, 0.3 m
KABETH11	Patch cable, RJ45 UTP CCA, CAT5e white, 1 m
KABETH12	Patch cable, RJ45 UTP CCA, CAT5e white, 2 m

Drawings

Dimensions (mm):



UNIT: mm
Tolerance: ±0.5



Wachendorff Prozesstechnik GmbH & Co. KG
Industriestrasse 7 • 65366 Geisenheim
Germany

Phone: +49 (0) 67 22 / 99 65 - 20
E-Mail: wp@wachendorff.de
www.wachendorff-prozesstechnik.de

