

Mobilfunk-Antenne FAC91201_0000



- External omnidirectional mobile radio antenna
- Compact, space-saving design
- Mounting Hole in the control cabinet, wall or pole mounting via bracket
- 5 m connection cable with SMA plug
- Gain 2 to 7 dBi (depending on frequency range and alignment)

https://www.wachendorff-prozesstechnik.de/en/FAC91201_0000

Description

Omnidirectional mobile radio antenna for mounting in a control cabinet hole or using a mounting bracket for wall or pole mounting.

Product details

Interfaces:	1x SMA plug
Cable length:	5 meter CS29
Frequency ranges:	617 to 960 MHz 1710 to 2700 MHz 3400 to 3800 MHz 4900 to 6000 MHz
Antenna gain:	2 dBi (at 617 to 960 MHz) 3.5 dBi (at 1710 to 2700 MHz) 5 dBi (at 3400 to 3800 MHz) 7 dBi (at 4900 to 6000 MHz)
Impedance:	50 Ohm
Art:	Omnidirectional antenna
Weight:	390 g
Dimensions:	H x W: 164 mm x Ø 48 mm
Protection class:	IP66
Ambient temperature:	Operation: -40 °C to +85 °C Storage: -40 °C to +85 °C
Assembly:	Mounting in switch cabinet hole (M12), wall or pole mounting via bracket

Products Order no.

ECCAIRC01	Extension cable mobile phone antenna 1 meter
ECCAIRC03	Extension cable for mobile phone antenna 3 meters
ECCAIRC05	Mobile phone antenna extension cable 5 meters



Wachendorff Prozesstechnik GmbH & Co. KG
Industriestrasse 7 • 65366 Geisenheim
Germany

Phone: +49 (0) 67 22 / 99 65 - 20
E-Mail: wp@wachendorff.de
www.wachendorff-prozesstechnik.de

